

Machine Tools

LYCK8463

Max diameter of workpiece: $\Phi 630\text{mm}$
Rotating speed of spindle: 4-285r/min

- ✓ Fit to handle large rolls like special steel
- ✓ CNC vertical turret tool holder with less tool-to-tool time and long service life
- ✓ Take real-time monitoring of all key components
- ✓ The auto-protecting function used to avoid unforeseen accidents
- ✓ Realize intelligent and user-friendly operation



Model	LYCK8463
Positioning Accuracy (mm)	X axis:0.0165; Z axis:0.05
Repositioning Accuracy (mm)	X axis:0.006; Z axis :0.013
Max Diameter of Workpiece (mm)	$\Phi 630$
Max Length of Workpiece (mm)	3000
Distance Between Centers (mm)	3300
Taper Hole of Spindle	Metric #140 (taper: 1:20)
Diameter of Front Bearing Cone of Spindle (mm)	$\Phi 200$
Max Output Torque of Spindle (N·m)	3700
Rapid Moving Speed (mm)	X axis:10; Z axis: 7
Max Stroke (mm)	X axis: 425; Z axis: 3000
Total Footprint (L*W, mm)	7430*2489
Power Supply	Three-phase 380V, 50Hz/60Hz (custom-made)